

Premcrete

n55Plus



## Prem-Base 760

By Premcrete

### Detailed description

Free flowing, protein free, self-smoothing industrial flooring underlayment system, which is obtained by mixing water with a selected pre-blended formulation utilizing high quality raw materials.

Features/ Benefits:

- Ease of application by pump or manually.
- Rapid drying characteristics facilitate rapid return to service.
- Two to four hour walk on time.
- An efficient method of levelling and renovating old floors in preparation for final floor coating.
- Low odour.
- Self-smoothing and highly fluid.

Applications:

Used to complement Prem-Top 720 and provide an economic means of raising and smoothing industrial floors.

Priming:

Substrates should be primed using Premcrete Tackprimer, blinded with 8/16's grade sand.

### Product guidance - As Standard

Application thickness:

5–60 mm.

Colour:

Light grey.

Technical properties:

- Compressive strength: 30 MPa (28 days).
- Flexural strength: 8.5 MPa (28 days).
- Controlled expansion: 0.025% (28 days).

### Product specification

Manufacturer

- Name: Premcrete

- Web: [www.premcrete.com](http://www.premcrete.com)  
- Email: [sales@premcrete.com](mailto:sales@premcrete.com)  
- Tel: +44 (0)2380 276 166  
- Address: Seymour House, Mayflower Close, Chandlers Ford, Eastleigh, Hampshire SO53 4AR

Product reference Prem-Base 760