

Premcrete

n55Plus



Prem-Top 720

By Premcrete

Detailed description

Free flowing, protein free, self-smoothing industrial flooring system, which is obtained by mixing water with a selected pre-blended formulation utilizing high quality raw materials.

Features/ Benefits:

- Ease of application by pump or manually.
- Rapid drying characteristics facilitate rapid return to service.
- Two to four hour walk on time.
- Excellent abrasion and impact resistance.
- Low odour.
- Self-smoothing and highly fluid.
- Laying rates in excess of 1000 m² per day can be achieved.
- Suitable for use as a final wearing surface.

Applications:

For use where heavy industrial traffic is to be utilized and for warehouse racking aisles.

Priming:

Substrates should be primed using Premcrete Tackprimer, blinded with 8/16's grade sand.

Product guidance - As Standard

Application thickness:

6–20 mm.

Colour:

Light grey.

Technical properties:

- Density (dry): 1700 kg/m³.
- Compressive strength: 32 MPa (28 days).
- Flexural strength: 9 MPa (28 days).
- Controlled expansion: 0.025% (28 days).

Product specification

Manufacturer

- Name: Premcrete
- Web: www.premcrete.com
- Email: sales@premcrete.com
- Tel: +44 (0)2380 276 166
- Address: Seymour House, Mayflower Close, Chandlers Ford, Eastleigh, Hampshire SO53 4AR

Product reference Prem-Top 720