

Premcrete

n55Plus



Epocote SF

By Premcrete

Detailed description

A solvent-free epoxy coating designed to provide decorative and protective properties to concrete, steel and other substrates. The material is supplied as a two pack system comprising of pre-weighted base and curing agents. After mixing together, it is easily applied to produce a chemical and abrasion resistant finish.

Features/ Benefits:

- Solvent free, low odour.
- Excellent chemical resistance.
- Excellent adhesion to concrete and steel.
- High build abrasion resistant.
- Hygienic and easily cleaned.
- Tough and durable.

Applications:

Used as a waterproof, tough, chemical resistant floor or wall coating in food preparation areas, breweries, abattoirs, etc. It can also be used as an internal lining for concrete or steel storage tanks containing oils, chemicals, water, etc. It is particularly suitable for chemical bunds.

Priming:

Primer is not required when applying to asphalt and tarmac surfaces. Concrete surfaces should be primed with a coat of Epoprime W.

Product guidance - As Standard

Technical properties:

- Adhesive strength: To concrete: 3.9 MPa; To carbon steel: 12 MPa.
- Drying time: Tack free: Five hours; Hard dry: 12 hours.

Product specification

Manufacturer

- Name: Premcrete
- Web: www.premcrete.com

- Email: sales@premcrete.com
- Tel: +44 (0)2380 276 166
- Address: Seymour House, Mayflower Close, Chandlers Ford, Eastleigh, Hampshire SO53 4AR

Product reference Epocote SF

Colour Grey
Red
Special order - Insert BS 4800 or RAL colour requirement.